

ON SERIES® WALLMOUNT EXTENDED RUNTIME UPS: For many, conventional UPSs are “good enough.” But some find ordinary protection measures inadequate. Others face performance expectations with no tolerance for downtime. ON Series Power Conditioned UPSs are engineered to satisfy these demanding applications.

Ultimate assurance of system reliability

All UPS makers acknowledge the broad range of power disturbances that compromise system reliability. And all address them to some degree. But here's the difference — ONEAC's proprietary power conditioning technology eliminates power problems entirely. Providing a level of protection that even the highest quality surge suppressor and filter technology cannot match.

Exceptionally dependable battery backup


We start with premium quality batteries. Thermally isolate them for maximum life. And employ unique charging circuitry attuned to the specific battery characteristics of each model to speed recovery and minimize stress on batteries. Automatic monitoring of battery condition ensures readiness, gives plenty of warning when replacement is recommended. And our patented battery pack allows replacement in under a minute without tools or training, without downtime, and without risk.

Proven durability, backed by a 5-year warranty

ONEAC UPS's robust design is impervious to the harshest electrical environments. Designed and manufactured under ISO9001 quality procedures, ON Series UPSs are exceptionally reliable. With an average mean time between failures more than twice as long as leading competitors. No surprise, then, that we back our UPSs with greater confidence — 5 years on all power and control systems, 2 years on the battery sub-system.



ONEAC's low-impedance, isolation transformer provides a level of protection superior to surge suppressor and filter based systems — provides greater assurance of system reliability.



- **Extended runtime:** provides up to 8 hours of battery backup time
- **Wall mountable:** for applications with space constraints
- **Full-time, on-line isolating transformer:** eliminates all power contaminants
- **Sinusoidal waveform:** supports even the most sensitive loads
- **ONBoost™:** compensates for momentary voltage drops, conserves batteries
- **Intelligent serial communications:** for advanced diagnostics & remote management
- **On-site, on-line replaceable battery:** minimizes cost and downtime
- **Automatic self test:** ensures battery and system readiness
- **5-year Warranty:** the best assurance of product quality and performance in the industry

ON SERIES WALLMOUNT EXTENDED RUNTIME UPS: Specifications

Power Conditioning

ONEAC's unique power conditioning architecture provides superior protection against the full range of power line disturbances. Components include:

Full output isolation: ONEAC's proprietary transformer design integrates power conditioning magnetics and voltage conversion magnetics in a single compact unit. Provides superior protection against lightning and other high energy surges.

Virtual Kelvin Ground®: Eliminates the full spectrum of conducted power line noise (from 50 kHz to 10 MHz) in all modes, reduces the effect of electrostatic discharge (ESD) and provides an exceptionally clean signal reference ground for electronic systems.

Communications

Basic mode provides standard protocols recognized by UPS monitoring software supplied with Windows NT, NetWare and Banyan operating systems.

Advanced mode uses ONEAC's content-rich ASCII packets to communicate with ONEAC's MopUPS® family of UPS monitoring software for NetWare, OS/2, a full catalog of UNIX operating systems and SNMP.

Global Approvals

Models for North America are FCC Class A certified and listed under UL 1778 and CSA22.2 safety standards. Models for Europe carry the GS and CE marks and are tested under the following standards: EN50091, EN60950, EN50081-1, EN55022 (CISPR 22), EN50082-1, IEC801-2, IEC801-3 and IEC801-4.

Performance Characteristics

Nominal input voltage: 120 Vac, 60 Hz & 230 Vac, 50/60 Hz

Surge voltage withstand capability: ANSI/IEEE C62.41 Category A&B, 6 kV/200 & 500 Amp, 100 KHz ringwave

Surge voltage let-through (max): Less than 10V Normal mode (L-N), less than 0.5 V Common mode (N-G) when subjected to 6kV ANSI/IEEE C62.41 Cat. A

Normal & common mode clamping response time: Instantaneous

Transfer time (typical/max): < 3.0 / 3.5 milliseconds

On-battery output voltage: Sine wave

ONBoost™: boosts output voltage 11% above input voltage if between -21% & -15% of nominal

Load power factor range (crest factor): UPS .65 to 1.0 (3) — will support loads rated 0.5 to 1.0 (<5)

Batteries: sealed, maintenance-free lead acid with a 3-6 year typical lifetime

Recharge time to 60% available capacity: 4 hours per battery cabinet


All units have temperature sensitive chargers and provide thermal isolation for battery pack.

SERIES	ON 400	ON 600	Battery Cabinet
Maximum Capacity (volt-amps, watts)	400, 280	600, 400	n/a
Batteries	n/a	n/a	two 12V, 17AH
Maximum dimensions (H)	15" (38 cm)	15" (38 cm)	7.5" (27 cm)
Maximum dimensions (W)	8.5" (22 cm)	8.5" (22 cm)	8.5" (22 cm)
Maximum dimensions (D)	9" (23 cm)	9" (23 cm)	9" (23 cm)
Net weight— lbs. (50Hz in kg)	25 (13)	29 (15)	35 (16)
Shipping weight— lbs. (50Hz in kg)	30 (15)	34 (17)	40 (18)
Input connector <i>Other plugs and sockets available upon request.</i>	5-15P	5-15P	battery sensor cable
Output sockets: NEMA 5-15R for 60Hz (IEC 320 female for 50Hz)	4	4	n/a

NUMBER OF BATTERY CABINETS		1	2	4	6	8
POWER HEAD REQUIRED	VA LOAD	RUNTIME (HOURS:MINUTES)				
ON400	100	3:15	6:44	14:08		
ON600	200	1:53	3:56	8:25		
ON600	400	0:55	2:00	4:29	6:33	9:05
ON600	600	0:29	1:11	2:47	3:50	5:28

ONEAC, ONSeries, ONBoost, Virtual Kelvin Ground and MopUPS are trademarks of ONEAC Corporation. All other trademarks, product and corporate names are the property of their respective owners.

A CHLORIDE POWER PROTECTION COMPANY



All ONEAC-manufactured products are Y2K compliant.

ONEAC is a UL/BSI registered corporation — Certification No. A2900



(800) 327 8801 EXT. 2 in USA AND CANADA

+44 0 1235 534721 in UK AND EUROPE

27944 N. Bradley Road, Libertyville, IL 60048 Phone 847 816-6000 FAX 847 680-5124

18 & 20 Blacklands Way, Abingdon Business Park, Abingdon, Oxfordshire OX14 1DY, UK FAX +44 (0) 1235 534197